

# Geo\electric AG

Antriebssysteme

## GEO-TM-TAI Series



Appendix						
CODE	Rated Load		SELF LOCKING G KG (PUSH)	Typical Current at Rated Load (A)	Typical Speed	
	PUSH KG	PULL KG			No Load (32VDC) mm/s	Rated Load (24VDC) mm/s
<b>Standard Motor (2600RPM)</b>						
C	500	400	250	3.6	7.2	3.9
D	600	400	400	3.5	5.5	2.9
F	250	250	100	3.4	14.4	8.9
G	200	200	100	3.8	19.2	10.8
H	100	100	50	3.4	28.8	17.6
J	350	350	350	3.8	9.6	5.7
K	800	400	600	4	4.5	2.5
<b>Fast Motor(3400RPM)</b>						
L	600	400	400	4.4	7.3	3.9
N	250	250	100	4.2	19.2	11.8
O	200	200	100	4.6	25.6	13.8
P	100	100	50	4.2	38.4	23.4
Q	350	350	350	4.6	12.8	7.6
R	800	400	600	5	6.5	3.3
T	500	400	250	4.2	9.7	5.1
<b>Long Motor(3800RPM)</b>						
X	600	400	400	4.4	7.8	5.2
Y	800	400	600	5.3	7	4.4
B	1000	400	1000	6.3	5.5	2.7



